

## 热塑性橡胶/Thermoplastic rubber E-346

### 1. 产品描述/Product Description

热塑性弹性体 E-346 是苯乙烯含量为 22% 的线性嵌段共聚物。E-346 为高 MFR 的高双嵌段聚合物。E-346 用于配制压敏胶和涂料，并用作沥青改性剂。

Thermoplastic Elastomer E-346 is a linear block copolymer with a styrene content of 22% mass, and it is a high diblock polymer with high MFR. E-346 is especially used for pressure sensitive adhesives and coatings as the bitumen modifier.

### 2. 典型性能/Typical properties

序号 No.	描述 Description	单位 Unit	典型值 Parameter	测试标准 Test Method
1	苯乙烯含量 Styrene content	wt. %	22	
2	二嵌段含量 Diblock content	wt. %	60	
3	熔体流动速率 (190°C/2.16kg) MFR (190°C/2.16kg)	g/10min	23	ASTM D1238-04
4	拉伸强度 Tensile strength	Mpa	1	ASTM D638
5	断裂伸长率 Elongation at break	%	1400	ASTM D412
6	邵氏硬度 Hardness	Shore A	10	ASTM D4703

### 3. 包装/Packaging

- 包装容器：聚乙烯袋  
Package: Polyethylene bags
- 包装规格：25kg/袋  
Weight: 25kg/ bag

### 4. 储存/Storage

存放于阴凉、干燥处。不建议长时间堆叠储存。不可存放于开口或者无标识容器中。  
Store in a cool and dry place. Long-term stacking storage is not recommended. Do not store in open or unlabeled containers.