

石油树脂/ Hydrocarbon Resin RES-500-C45XL

1. 产品描述/Product Description

- RES-500-C45XL 属于脂肪烃石油树脂，由不饱和烯烃聚合而成。用于热熔路标漆，具有颜色浅、热稳定性好、流动性一致，强粘结性、高硬度和持久耐磨性。
- RES-500-C45XL is an aliphatic hydrocarbon resin, polymerized by unsaturated olefins, which is used for hot melt road marking paint. The resin has the characteristics of light color, good thermal stability, good flow consistency, strong bond strength, high hardness and high durable wear resistance.

2. 典型性能/Typical properties

序号 No.	项目 Item	参数 Parameter	标准 Standard
1	软化点 (环球法, °C) Softening Point (Ring & Ball, °C)	98~104	ASTM E 28
2	颜色 Color	≤4.5	ASTM D 1925
3	分子量-数均 (Mn) Molecular Weight (Mn)	1400	GPC

3. 包装/Packaging

- 包装容器：聚乙烯袋
Package: Polyethylene bags
- 包装规格：25kg/袋
Weight: 25kg/ bag

4. 储存/Storage

存放于阴凉、干燥处。不建议长时间堆叠储存。不可存放于开口或者无标识容器中。
Store in a cool and dry place. Long-term stacking storage is not recommended. Do not store in open or unlabeled containers.