

石油树脂/ Hydrocarbon Resin RES-500-C50S

1. 产品描述/Product Description

RES-500-C50S 属于脂肪烃石油树脂，是由不饱和烯烃聚合而成，用于热熔路标漆中，该树脂颜色浅、热稳定性好，具有流动一致性、涂层附着力强、硬度高、耐磨性好的特点。

RES-500-C50S is an aliphatic hydrocarbon resin, polymerized by unsaturated olefin, which is used for hot melt road marking paint. It has the characteristics of light color, good thermal stability, flow consistency, excellent coating adhesion, high hardness and durable wear resistance.

2. 典型性能/Typical properties

序号 No.	项目 Item	参数 Parameter	标准 Standard
1	软化点 (环球法, °C) Softening Point (Ring & Ball, °C)	98~106	ASTM E 28
2	颜色 Color	≤5.0	ASTM D 1925
3	熔融粘度 (BRF, @200°C, cp) Melt Viscosity (BRF, @200°C, cp)	≤250	ASTM D 3236

3. 包装/Packaging

- 包装容器：聚乙烯袋
Package: Polyethylene bags
- 包装规格：25kg/袋
Weight: 25kg/ bag

4. 储存/Storage

存放于阴凉、干燥处。不建议长时间堆叠储存。不可存放于开口或者无标识容器中。
Store in a cool and dry place. Long-term stacking storage is not recommended. Do not store in open or unlabeled containers.