

石油树脂/ Hydrocarbon Resin RES-515-C80

1. 产品描述/Product Description

RES-515-C80 属于脂肪烃石油树脂，由不饱和烯烃聚合而成，应用于橡胶基、EVA 基等胶黏剂中，体现胶的高粘结强度和耐高温性能。

RES-515-C80 is an aliphatic hydrocarbon resin, polymerized by unsaturated olefins, which is used for rubber based and EVA based adhesives, improving the bond strength and temperature resistance.

2. 典型性能/Typical properties

序号 No.	项目 Item	参数 Parameter	标准 Standard
1	软化点 (环球法, °C) Softening Point (Ring & Ball, °C)	110-118	ASTM E 28
2	颜色 Color	≤8.0	ASTM D 1925
3	熔融粘度 (BRF, @180°C, cp) Melt Viscosity BRF, @180°C, cPs	1300	ASTM D 3236

3. 包装/Packaging

- 包装容器：聚乙烯袋
Package: Polyethylene bags
- 包装规格：25kg/袋
Weight: 25kg/ bag

4. 储存/Storage

存放于阴凉、干燥处。不建议长时间堆叠储存。不可存放于开口或者无标识容器中。

Store in a cool and dry place. Long-term stacking storage is not recommended. Do not store in open or unlabeled containers.