

C9 热聚石油树脂/C9 Thermal Hydrocarbon Resin RES-900-C100

1. 产品描述/Product Description

本产品用裂解 C9 原料，经热聚合生产制得，为黄色或淡黄色颗粒状固体，具有良好的热稳定性、相容性、耐水、耐酸碱。

RES-900-C100 is made by cracked C9 through thermal polymerization. It is yellow or light yellow granular solid, with good heat stability, solubility, water resistance and acid/alkaline resistance. And it is mainly used as adhesive assistant agent in rubber industry.

2. 典型性能/Typical properties

序号 No.	项目 Item	参数 Parameter	标准 Standard
1	软化点 (环球法, °C) Softening Point (Ring & Ball, °C)	90-100	ASTM E 28
2	颜色 Color	9.5-10.4	Gardner

3. 包装/Packaging

- 包装容器：聚乙烯袋/牛皮纸袋
Package: Polyethylene bags/ Kraft paper bags
- 包装规格：500-700kg/袋或 25kg/袋
Weight: 500-700kg/bag or 25kg/bag

4. 储存/Storage

本品应室内储存，注意防火、防晒、防雨、放手钩，且环境温度不超过 35°C，相对湿度不大于 85%。

This product should be stored indoor, and pay attention to fire prevention, sun protection and rain protection. The room temperature must not higher than 35°C, and the humidity must not higher than 85%.